

SonicPoint

- Compact 10.4 inch screen
- Bright TFT colour display
- Integrated touch screen
- Graphical user interface
- Ruggedized aluminum case
- Sealed enclosure
- Water and dust resistant
- Windows® XP Embedded
- No moving parts
- Wireless networking ready
- Low heat/power consumption
- Industrial-grade external connectors

The SonicPoint by Manusonic provides your workforce with an efficient point-of-entry system and includes advanced communication features that can send notices and alerts to your employees.

Workforce Automation: SonicPoint's centralized data base allows supervisors access to real-time attendance information.

Construction: SonicPoint's durable aluminum enclosure prevents rust and corrosion. The sealed case along with IP-rated external connectors protect the components from humidity and dust.

Display: The 10.4 inch colour LCD and industrial-grade touch screen offer easy viewing and error-free operation, even in harsh environments.

Alerts: Audible and Visual alerts notify the user with sign-in status and can be used to communicate messages during the sign-in/out process.

Biometric Security: Eliminate "buddy punching" using the biometric finger scanning option. SonicPoint's embedded sensor validates employee identity through an advanced verification process that stores a mathematical interpretation of the fingerprint as opposed to the actual image.

Networkability: Installing SonicPoint in your company is as easy as installing an additional desktop computer. A standard RJ45 Ethernet connection allows for a quick connection to your existing computer network. Each data collection device communicates with the central database allowing seamless access from any location. A wireless networking option is also available.

Employee Access: Expedite the daily clock-in/out process using the built-in proximity card reader. Multiple card styles and options are available.



SonicPoint

SonicPoint features & benefits:

- Centralized data collection provides real-time information
- Fast sign-in using proximity scanner
- Visual / Audio feedback to indicate clock-in/out status
- Large easy-to-use interface minimizes errors

Technical Specifications

Operating System

- Windows XP Embedded

Display

- Integrated flat panel LCD
- Standard resolution (10.4" Model): 800 × 600

Touch Screen

- Durable Projective Capacitive technology
- Industrial-grade glass surface

Network

- 10/100 Base-T Compatible

Construction

- Water-tight aluminum enclosure
- IP65-rated external connectors
- Wear-resistant powder-coat finish (Black)
- Easy wall-mount installation

Dimensions

- Case size: 12.5" W x 10.5" H x 3.5" D
- Screen area: 8.32" W x 6.24" H